

## Advanced Circuits' Capabilities

### Material

#### FR-4

Standard FR4	40 Layers
Isola FR406	40 Layers

#### Halogen Free

Isola Green Speed	40 Layers
Ventec VT-441, VT-447	40 Layers

#### RoHS

ITEQ IT-180A	30 Layers
Isola 185HR	30 Layers
Isola 370HR	40 Layers
Isola IS410 (CAF Resistant)	40 Layers
Isola FR408 and FR408HR	40 Layers
Isola I-TERA MT	40 Layers
Isola BT-IS620	30 Layers
Nelco BT-N5000	30 Layers
Nelco 4000-29	40 Layers
Nelco 4000-13 and 13SI	40 Layers
Nelco 4000-13EP and EPSI	40 Layers
Isola IS415 (CAF Resistant)	40 Layers
Polyimide	40 Layers
Cyanate Ester	20 Layers

#### RF Materials

Rogers 3000 Series	Max. 20 lyr. FR-4 w/ RO3000 Caps
Rogers 4000 Series (4003 and 4350)	20 Layers
Rogers 5870/5880	8 Layers
Taconic RF Materials	2 Layers
Isola Astra MT	40 Layers
Isola Tachyon	40 Layers

#### Advanced RF Materials

Nelco 9000 Series (PTFE)	2 Layers
Rogers 6000 Series	4 Layers
Rogers 5000 Series	2 Layers
Rogers Diclad 880, AD300A, CuClad, 250 & 233, CTLE	20 Layers
Arlon Genclad 280, LX250, GYN 2.17 Dk	10 Layers

#### Expanded Materials Used For Signal Integrity, Advanced HDI, and/or Stacked Microvias

Panasonic Megtron 6	Yes
Zeta Lam SE	Yes
3M ECM (Embedded Capacitance Material)	Yes
ROHACELL	Yes (12 layer)
Rogers 2929 Bondply	Yes
Arlon 6700 and 6250 Bondply	Yes

### Maximum Useable Panel Area

For 12" x 18" Panel	10" x 16" ***
For 18" x 24" Panel	16.6" x 22" ***
For 18" x 27" Panel	16" x 25" *
For 18" x 32" Panel	16" x 30" *
For 18" x 36" Panel	16" x 34" *
For 18" x 42" Panel	16" x 40" *
For 18" x 54" Panel	16" x 52" *
For 21" x 24" Panel	19" x 22" **
For 21" x 60" Panel	18" x 58" *
For 24" x 30" Panel	22" x 28" *

\* Up to 8 Layers / \*\* Up to 30 Layers / \*\*\* Up to 40 Layers

### Special Products/Unique Capabilities

Heavy Copper	Up to 20 oz.
Heatsinks	Available
Backplates	Available
2 Layers up to 37" x 96" Panel w/ NPT's	Available
ROHACELL Foam Bonding	Available
Buried Chips and Resistors	Available
Resistance and Conductance Test Equipment	Available

### Stack-Ups

#### Overall Thickness Range and Tolerances

Overall Board Thickness	0.010" - 0.250"
<b>Overall Board Thickness Tolerances</b>	
< 0.020"	Standard +/- 0.004" Special +/- 0.003"
0.031"	Standard +/- 0.004" Special +/- 0.003"
0.062"	Standard +/- 0.006" Special +/- 0.004"
0.093"	Standard +/- 0.009" Special +/- 0.006"
0.125"	Standard +/- 0.012" Special +/- 0.009"
0.187"	Standard +/- 0.018" Special +/- 0.014"
0.250"	Standard +/- 0.025" Special +/- 0.018"

#### Thinnest Dielectric Finished

Thin Board Overall Thickness:	0.010" (2 Layer) 0.015" (4 Layer)
Thinnest Plated Core	0.004"

# Mechanical Capabilities

<b>Machining Drill Capabilities</b>	
Primary Drilled Hole Location Tolerance to Datum Zero (DTP)	0.005"
2nd Drill Hole Location Tolerance to Datum Zero (DTP)	0.005"
Minimum Clearance from Copper Conductor to Mechanical Drilled Hole	0.006"
Minimum Clearance from Copper Conductor to a Laser Drilled Hole	0.004"
<b>Plated Through Hole Capabilities</b>	
<b>Smallest Plated Through Hole Size with 0.001" Minimum Average Copper Requirement</b>	
Finished Panel Thickness < 0.020"	0.003" Finished Hole
Finished Panel Thickness 0.031"	0.003" Finished Hole
Finished Panel Thickness 0.062"	0.004" Finished Hole
Finished Panel Thickness 0.093"	0.008" Finished Hole
Finished Panel Thickness 0.125"	0.010" Finished Hole
Finished Panel Thickness 0.187"	0.012" Finished Hole
Finished Panel Thickness 0.250"	0.018" Finished Hole (Excluding HAL Finish)
Plated Hole Size Tolerance	+/- 0.003" Standard; Special +/- 0.002"
Plated Hole Size Press Fit Applications	+/- 0.002" Typical
Aspect Ratio (with 0.010" Drill)	18:1 (0.007" Finish in 0.130" Thick)
Plated Hole Spacing Minimum (Drilled Hole to Hole)	0.008"
<b>Non Plated Through Holes</b>	
Smallest Non-Plated Hole Size	0.006"
Largest Non-Plated Hole Size Routed	No Limit
Non-Plated Routed Hole Tolerance	+/- 0.005" Typical +/- 0.003" Special
Minimum NPTH to Edge of Board Spacing	0.010"
<b>Blind/Buried Vias (Sequential Lamination)</b>	
Minimum FINISHED Via Hole Diameter - Epoxy Filled	0.008"
Maximum FINISHED Via Hole Diameter - Epoxy Filled	0.02"
Maximum Aspect Ratio for Epoxy Filled Via Holes	10:1
Available Epoxy Fill Types	Conductive & Non-Conductive

<b>HDI / Laser Microvia (<math>\mu</math>Via) Capabilities</b>	
Smallest (as ablated) Laser Via	0.003"
Largest (as ablated) Laser Via	0.010"
Via Aspect Ratio (Depth to Diameter)	0.75:1 Standard 1:1 Advanced
Capture Pad Size	$\mu$ Via +0.008" Std $\mu$ Via +0.006" Adv
Landing Pad Size	$\mu$ Via +0.008" Std $\mu$ Via +0.006" Adv
Stacked Via	Yes
Type I Capabilities	Yes
Type II Capabilities	Yes
Type III Capabilities	Design Dependent
Copper Filled Microvia	Yes
<b>Control Depth / Drill Capabilities</b>	
Backdrill - PTH Stub Removal	PTH + 0.010" Diameter (Typical)
Minimum Backside Dielectric Separation	0.005"
Minimum Back Drill Diameter	0.014"
Drill Depth Tolerance	0.005" Typical, 0.004" Minimum
<b>Scoring Capabilities</b>	
Angles	Standard 30° Available 20°, 45°, & 60°
Offset Tolerance	+/-0.005"
Optimum Remaining Web Thickness	Typical Maximum 1/3 of thickness
Remaining Web Tolerance	+/-0.005"
True Position Tolerance	+/-0.005"
<b>Edge Connector Bevel Capabilities</b>	
Finger Tip Angle	15°, 20°, 30°, 45°
Bevel Depth Tolerance	+/-0.005"
<b>Profile Capabilities</b>	
Standard Router Bit Diameter	0.093", 0.062", 0.031" (Router Bits) Special 0.021"
Routed Profile Tolerance	+/-0.005" Standard +/-0.004" Special
Minimum Internal Rout Radius	0.015"
Minimum Routed PTH Slot Width	0.022" Typical with 0.015" Minimum



## Feature Size Capabilities

### Internal Layer Capabilities

Minimum Conductor Width and Spacing	
Internal Starting Copper Weight 1/2 oz.	0.00275" Line / 0.003" Space
Internal Starting Copper Weight 1 oz.	0.00375" Line / 0.0045" Space
Internal Starting Copper Weight 2 oz.	0.005" Line / 0.006" Space
Internal Starting Copper Weight 3 oz.	0.009" Line / 0.011" Space
Internal Starting Copper Weight 4 oz.	0.012" Line / 0.016" Space

### External Layer Capabilities

Minimum Conductor Width and Spacing	
External Copper Finished Thickness 1.0 oz.	0.00275" Finished
External Copper Finished Thickness 1.5 oz.	0.004" Finished
External Copper Finished Thickness 2.0 oz.	0.005" Finished
External Copper Finished Thickness 3.0 oz.	0.009" Finished
External Copper Finished Thickness 4.0 oz.	0.011" Finished
External Copper Finished Thickness 5.0 oz.	0.020" Finished
External Copper Finished Thickness 6.0 oz.	0.030" Finished
External Copper Finished Thickness 7.0 oz.	0.045" Finished
External Copper Finished Thickness 8.0 oz.	0.060" Finished

### Pad Diameter to Drilled Hole Size

#### IPC-6012 Class 2

Component Holes	Drilled Size Plus 0.010"
Via Holes	Drilled Size Plus 0.008"

### Pad Diameter to Drilled Hole Size

#### IPC-6012 Class 3/3A

Component Holes	Drilled Size Plus 0.012"
Via Holes	Drilled Size Plus 0.010"

### Pad Diameter to Laser Ablated Hole Size

Minimum	Drilled Size Plus 0.004"
Standard	Drilled Size Plus 0.008"

## Military

### Etch Back

Yes

IPC Class 3 Etchback Specification 0.0002"-0.002"

## Solder Mask and Legend

### Solder Mask

Min. LPI Solder Mask Clearance (Standard)	0.002" / Side (Pad Size + 0.004")
Min. LPI Solder Mask Clearance (LDI Imaged)	1:1 (Design Dependent)
Pad Size Larger than NPTH	0.005" / Side (Pad Size + 0.010")
Web Between Surface Mount Pads	0.004" Preferred, 0.003 Minimum (Green)
Solder Mask Colors	Green, Blue, Red, Black, Yellow, White, Orange, Purple, Pink, Brown, Clear, Matte Green & Matte Black
Solder Mask Type	Liquid Photo Imageable Laser Direct Imaging (Special)
Min. Mask Defined Pad Diameter	0.005"
Solder Mask Plugged Vias	Yes

### Legend

Printed Legend Minimum Stroke/Width	0.005"
LPI Legend Capability	Yes
LPI Legend Minimum Stroke/Width	0.002"
Screened / LPI Legend Colors	White, Black, Yellow, Red, Blue
Serialization / Unique Serialization	Yes

## Surface Finish Options

### Surface Finish Selection

Hot Air Solder Level (Lead Free, Lead Based)	Yes
Immersion Silver	Yes
OSP	Yes (Outsource)
Electroless Nickel Immersion Gold	Yes
ENEPIG	Yes
Immersion Tin	Yes (Outsource)
Full Body Gold	Yes
Bondable Gold	Yes (Outsource)
Plated Nickel	Yes
Electroless Nickel	Yes
Copper	Yes
Hot Oil Reflow	Yes

### Mixed Finishes

HASL with Selective Gold	Yes
Dual Gold Plating	Yes
Immersion Gold w/ Selective Hard Gold on Fingers	Yes
Recessed Fingers	Yes



## Via-in-Pad

Epoxy Filled Thru Hole Capability	Yes
Epoxy Filled Thru Hole Minimum	0.004" FHS
Epoxy Filled Thru Hole Maximum	0.020" FHS
Minimum Board Thickness	0.020"
Maximum Board Thickness	0.125"
Via Fill Aspect Ratio	10:1
Conductive VIP Options	Yes
Non-Conductive VIP Options	Yes

## Testing Capabilities

Minimum Test Continuity Resistance	.1 Ohms
Maximum Test Voltage	1000 Volts
Maximum Test Isolated Resistance	25 Mohm-2Gohm
Largest Test - Fixtured	16" x 22"
Largest Test - Flying Probe	27" x 24"
Electrical Test Pitch (Fixture Test)	0.020"
Electrical Test Pitch (Flying Probe Test)	0.004"
DC Line Resistance Testing	Yes

## Data & Documentation

### Tooling Formats

Film Data Formats	DXF, RS-274-x, RS-274-D, ODB++
Drill Data formats	ASCII, Excellon Format; RS-274-X, RS-274-D
Electrical Test Formats	IPC-D356
Netlist Compare Formats	IPC-D356 IPC-D356A

### Tooling Communication

Compression Formats	ZIP, TAR, TGZ
Secured Data Transfer Methods	Secure Data Transfer, PGP

The information provided in this sheet is subject to change without prior notice.

## Electrical Performance

TDR Test Tolerance (Print and Etch)	Standard 10%, Advanced 5%
TDR Test Tolerance (Plated Copper)	Standard 10%, Advanced 5%
TDR Test Tolerance Differential Measurements	Standard 10%, Advanced 5%
TDR Tolerance Single Ended Tolerance	Standard 10%, Advanced 5%
HiPot Testing (AC & DC)	Yes

## Quality Systems & Certifications

DOD Contracts | MIL-PRF-31032 | MIL-PRF-55110G  
AS9100C & ISO 9001:2008 Certified | JCP Registered  
IPC-6012 Class 2/3A Qualified | ITAR Registered  
UL Certified

*Leading the PCB Industry in Quality & Innovation*



### Tempe Division

229 S. Clark Drive  
Tempe, AZ 85281  
Phone: (800)678-0233  
Fax: (480)966-5896



### Aurora Division Corporate Headquarters

21101 E. 32nd Pkwy  
Aurora, CO 80011  
Phone: (800)979-4722  
Fax: (888)224-3291



### Maple Grove Division

8860 Zachary Lane North  
Maple Grove, MN 55369  
Phone: (763)424-3788  
Fax: (763)425-0999

[www.4PCB.com](http://www.4PCB.com)